RG - 12.5mm

Regular

GYPSUM BOARD 09 29 00/GC



Description

The Gypsemna's **REGULAR (RG - 12.5mm)** Type C Gypsum Board is an interior gypsum board consisting of a solid set, Type C gypsum core enclosed in GRAY-colored face paper and a strong liner back paper. Gypsemna's RG Type C board. Long edges are slightly tapered, allowing joints to be reinforced and concealed with joint tape and joint compound. The face paper and the back paper are 100 percent recycled.



Basic Uses

The Gypsemna's REGULAR (RG - 12.5mm) Type C Gypsum Board is used for interior walls and ceilings in all buildings categories applications. It can be used for new construction or renovations steel framing. The boards are typically screwed to studs spaced maximum (600 mm) also can be applied by laminating or with the use of an adhesive.



Advantages

- Consistently high quality.
- Uniformly flat, attractive appearance, no shadows
- High edge hardness.
- Uniform high-strength cores eliminate crumbling, cracking.
- Edge tapers consistent to form perfect joints.
- Excellent thermal barrier and sound attenuation qualities.
- Green certified.
- Qualifies as a low-VOC



Technical Data

Physical Properties

Thickness, Nominal 12.5mm
Width, Nominal 1200mm

Length, Standard 2400mm, 3000mm

Weight, Nominal 8.60kg/m2

Edges TE, SE

Color Gray Color

Fire-Resistance Characteristics ASTM E84

Core Type Type 0

Combustibility Non-combustible Core

Surface Burning Characteristics Class A

Flame Spread 0

Smoke Development 15

Standards and References

- ASTM C1396 Product Standard Compliance

- ASTM C473 Standard Test Methods for

Physical Testing of Gypsum Panel Products

- ASTM C840 Standard Specification for

Application and Finishing of Gypsum Board

- ASTM E84 Standard Test Method for Surface

Burning Characteristics of Building Materials

- EN 520 Type A, Performance of Gypsum.

Plasterboards

Get in touch

