

# SP – 15mm

## Sound Protect

**GYPSUM BOARD**  
**09 29 00/GC**

### Description

Gypsemna's **SOUND PROTECT (SP - 15mm)** Type X Gypsum Board is an interior gypsum board consisting of a solid set, fire-resistive, Type X gypsum core enclosed in PURPLE-colored face paper and a strong liner back paper. Gypsemna's SP Type X board features a specially formulated core providing acoustic ratings when used in tested assemblies. Long edges are slightly tapered, allowing joints to be reinforced and concealed with joint tape and joint compound. The face paper and the back paper are 100 percent recycled.

### Basic Uses

The Gypsemna's SOUND PROTECT (SP - 12.5mm) Type X Gypsum Board is used for interior walls and ceilings in all buildings categories applications requiring acoustic performance ratings. It can be used for new construction or renovations steel framing. The boards are typically screwed to studs spaced maximum (600 mm) also can be applied by laminating or with the use of an adhesive.

### Advantages

- Acoustically tested .
- Fire ratings up to four hours.
- Consistently high quality.
- Uniformly flat, attractive appearance and no shadows.
- High edge hardness.
- Uniform high-strength cores Eliminate crumbling, cracking.
- Edge tapers consistent to form perfect joints.
- Excellent thermal barrier and sound attenuation qualities.
- Green certified.
- Qualifies as a low-VOC

### Technical Data

#### Physical Properties

Thickness, Nominal	15mm
Width, Nominal	1200mm
Length, Standard	2400mm, 3000mm
Weight, Nominal	12.6kg/m <sup>2</sup>
Edges	TE, SE
Color	Purple Color

#### Fire-Resistance Characteristics ASTM E84

Core Type	Type X
Combustibility	Non-combustible Core
Surface Burning Characteristics	Class A
Flame Spread	0
Smoke Development	15

#### Standards and References

- ASTM C1396 Product Standard Compliance
- ASTM C473 Standard Test Methods for Physical Testing of Gypsum Panel Products
- ASTM C840 Standard Specification for Application and Finishing of Gypsum Board
- ASTM E84 Standard Test Method for Surface Burning Characteristics of Building Materials
- ASTM E90 Standard Test Method for Laboratory Measurement of Airborne Sound Transmission Loss of Building Partitions and Elements
- EN 520 F & D Standard for performance of gypsum plasterboards

### Get in touch

[info@gypsemna.com](mailto:info@gypsemna.com)  
[www.gypsemna.com](http://www.gypsemna.com)

[technical@gypsemna.com](mailto:technical@gypsemna.com)  
[linkedin.com/company/gypsemna-company-llc/](https://www.linkedin.com/company/gypsemna-company-llc/)

