

# Flat Strap

# METAL

# PROFILES



## Description


Gypsemna Flat Strap is the horizontal member of the Ceiling / partition metal framework.

Applicable for Ceiling, Partition & Liner System

## Basic Uses

This is used primarily to back up the horizontal cut joints and also for lateral bracing. This also includes to provide support for seismic cross bracing and as backing strip for the fixation of Access Panel to the Ceiling / Partition system.

0.5, 0.80



50, 90, 150

## Advantages

- Consistently high quality.

## Technical Data

### Physical Properties

Coating	AZ150 Zinc- Aluminium Coating / Z275 Zinc Coating
Standard Compliance	ASTM A792 / ASTM A653
Steel Grade	G300
	Min. Yield Strength: 300 Mpa
	Min. Tensile Strength: 340 Mpa
Material	Cold roll-formed from hot-dipped galvanized steel
Thickness	0.50mm and 0.90mm
Width	50mm, 90mm and 150mm
Length	3000mm

## Get in touch

[info@gypsemna.com](mailto:info@gypsemna.com)  
[www.gypsemna.com](http://www.gypsemna.com)

[technical@gypsemna.com](mailto:technical@gypsemna.com)  
[linkedin.com/company/gypsemna-company-llc/](https://www.linkedin.com/company/gypsemna-company-llc/)

