

HANDYCOAT

JOINTING COMPOUND



Description

Handycoat is a ready to use filler for use on all common building surfaces, including timber. It gives a high quality, even surface for painting. Handycoat is specifically manufactured for the painter to repair and touch up exterior and interior surfaces, both new and old, prior to painting. It is designed for filling joints, hairline cracks etc. by hand application. Unlike conventional fillers, Handycoat has elastic properties, does not flake off, is permanent and retains its adhesion.

APPLICATION

Handycoat Exterior is suitable for exterior as well as interior surfaces. When dry, Handycoat Exterior and Wet Areas is weather resistant and bonds extremely well to cementitious materials, gypsum, gypsum boards, spray plaster, wood, galvanized and primed antirust steel surfaces etc. As a thin coat filler for patching hairline cracks in walls, ceilings, soffits, repair to damaged plasterwork, paintwork, filling holes and defects in woodwork, making good to exposed concrete, filling of dents in galvanized and anti-rust primed metal.

Advantages

- Styrene Acrylate
- Fine precisely graded fillers
- Dilution with water, if required
- 1.75 kg per liter density
- Negligible shrinkage
- Non-toxic Data
- 25 kg bucket packaging
- 12 months storage, (protected conditions) in original unopened containers

STANDARDS

- Product compliant to ASTM C 475/ C475M.
- Suitable to achieve finishing levels as per ASTM C 840.

Get in touch

info@gypsemna.com
www.gypsemna.com

technical@gypsemna.com
[linkedin.com/company/gypsemna-company-llc/](https://www.linkedin.com/company/gypsemna-company-llc/)

