



GYPSEMNA

MR BOARD

ACCESS PANEL
AP - 12.5 mm MR



■ DESCRIPTION

Gypsemna Access Panels are non-fire rated with a gypsum board face, which provide easy access to gypsum board ceilings and/or gypsum board partitions. Gypsemna Access Panel frames are manufactured from a stable Aluminum profile, which is white powder coated (RAL 9016). Gypsemna Access Panel has a flush fitted 12.5 mm Gypsemna Moisture Resistant Board infill. Gypsemna Access Panels are fitted with high quality concealed spring loaded push open and push close locking mechanisms and are fitted with a 1.5 mm laminated G.I wire with an eyelet hook for partial or full opening of the access panel door.

■ BASIC USES

Gypsemna's AP Access Panel Moisture Resistant Board is used for interior walls and ceilings for access to utilities and services.

■ ADVANTAGES

- Consistently High quality.
- Uniformly flat, attractive appearance, and no shadows.
- High Edge hardness.
- Uniform High strength cores eliminate crumbling and cracking.

■ TECHNICAL DATA

PHYSICAL PROPERTIES

Thickness, Nominal	15 mm
Width, Nominal	300 mm, 450 mm, 600 mm
Length, Standard	300 mm, 450 mm, 600 mm
Weight, Nominal	13.0kg +/-0.20 kg/m ²
Color	Green
Custom sizes	Available on request

■ STANDARDS & REFERENCES

- Complies with ASTM C 1396/C and ASTM C 1396/M
- Complies with EN 520, Types A and H1