



GYPSEMNA

RG BOARD

ACCESS PANEL
AP - 12.5 mm RG



■ DESCRIPTION

Gypsemna Access Panels are non-fire rated with a gypsum board face, which provide easy access to gypsum board ceilings and/or gypsum board partitions. Gypsemna Access Panel frames are manufactured from a stable Aluminum profile, which is white powder coated (RAL 9016). Gypsemna Access Panel has a flush fitted 12.5 mm Gypsemna Regular Board infill. Gypsemna Access Panels are fitted with high quality concealed spring loaded push open and push close locking mechanisms and are fitted with a 1.5 mm laminated G.I wire with an eyelet hook for partial or full opening of the access panel door.

■ BASIC USES

Gypsemna's AP Access Panel Regular Board is used for interior walls and ceilings for access to utilities and services.

■ ADVANTAGES

- Consistently High quality.
- Uniformly flat, attractive appearance, and no shadows.
- High Edge hardness.
- Uniform High strength cores eliminate crumbling and cracking.

■ TECHNICAL DATA

PHYSICAL PROPERTIES

Thickness, Nominal	15 mm
Width, Nominal	300 mm, 450 mm, 600 mm
Length, Standard	300 mm, 450 mm, 600 mm
Weight, Nominal	12.0kg +/-0.20 kg/m ²
Color	Grey
Custom sizes	Available on request

■ STANDARDS & REFERENCES

- Complies with ASTM C 1396/C and ASTM C 1396/M
- Complies with EN 520, Types A and H1